

BENGglas®

Solar Control

BENGGLAS



DOUBLE SOLAR
LOW E COATING
POS 2

CONSTRUCTIE | COMPOSITION | KONSTRUKTION | CONSTRUCTION

Buitenblad	
Exterieur	4T
Außen	
Outer pane	
Verdeler	0,3 Vacuüm
SZR	0,3 Vakuum
Intercalaire	0,3 Sous-vide
Spacer	0,3 vacuum
Binnenblad	
Intérieur	4T
Innen	
Inner Pane	

SPECIFICATIES | SPÉCIFICATIONS | SPEZIFIKATIONEN | SPECIFICATIONS

LTA		Lichttransmissie
TL	45-47	Transmission Lumineuse
LT		Lichttransmission
LT		Light transmission
BLR		Buiten lichtreflectie
RLE	15	Réflexion Lumineuse Extérieure
Lra		Lichtreflexion außen
ELR		External light reflection
LR (binnen)		Binnen lichtreflectie
RLI	17	Réflexion lumineuse Intérieure
Lri		Lichtreflexion innen
ILR		Internal light reflection
G-waarde		Zontoetredingsfactor
Valeur G	0,29	Facteur Solaire
G-wert		Gesamtenergiedurchlassgrad
G-value		Solar factor
EN674		U-waarde
Valeur U	0,50*	Valeur d'isolation
U-Wert		Dämmwert
U-value		Insulation value
EN ISO 10140-1 / 2		Geluidsdemping
RW (C ; Ctr) dB	36 (-2;-3)	Réduction du bruit
EN ISO 717-1		Lärmminderung
		Sound insulation

*U-waarde gebaseerd op EN 674:2011 en ISO 8302:1991 (TUV Rheinland, 2025).

* Valeur U basée sur EN 674:2011 et ISO 8302:1991 (TUV Rheinland, 2025).

*U-value based on EN 674:2011 and ISO 8302:1991 (TUV Rheinland, 2025).

* U-Wert basierend auf EN 674:2011 und ISO 8302:1991 (TUV Rheinland, 2025).



Netherlands

www.bengglas.nl

info@bengproducts.nl

+31 (0) 13 534 22 26

Belgium

www.bengglas.be

info@bengproducts.be

+32 (0) 19 60 08 31

